

TVC-23IRLP

HD TVI POC IR DOME



KEY FEATURES

- 2.0 megapixel high-performance CMOS
- HD analog output, up to 1080p resolution
- 2.8 mm fixed lens
- True Day/Night
- EXIR 2.0, smart IR, up to 20 m IR distance
- IP66
- PoC.af
- Up the coax



| SPECIFICATION | TVC-23IRLP |
|--------------------------|---|
| Camera | |
| Image Sensor | 2.0 megapixel progressive scan CMOS |
| Signal System | PAL/NTSC |
| Frame Rate | PAL: 1080p@25fps |
| Resolution | 1920 (H) × 1080 (V) |
| Min. illumination | 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50, 000 s |
| Lens | 2.8 mm fixed lens |
| Horizontal Field of View | 103.55° |
| Lens Mount | M12 |
| Day & Night | IR cut filter |
| Angle Adjustment | Pan: 0° to 360°, Tilt:0° to 75°, Rotate: 0° to 360° |
| Synchronization | Internal synchronization |
| Menu | |
| AGC | Low/middle/high |
| Day/Night Mode | Smart/color/BW(Black and White) |
| Backlight Compensation | Yes |
| DWDR | Yes |
| Language | English |
| Functions | Brightness, Sharpness, DNR, Mirror |
| Interface | |
| Video Output | 1 HD analog output/1 Vp-p composite output (75Ω/BNC) |
| General | |
| Operating Conditions | -40 °C to 60 °C, humidity: 90% or less (non-condens.) |
| Power Supply | 12 VDC ±30%/PoC.af |
| Power Consumption | Max. 4 W |
| Ingress Protection | IP66 |
| Material | Plastic |
| IR Range | Up to 20 m |
| Communication | Up the coax |
| Dimensions | Φ 110 mm × 93.2 mm |
| Weight | Approx. 350 g |



DIMENSIONS:

