

TWN-83MR

4 in 1 HD TVI BULLET



KEY FEATURES

- High performance CMOS, 8M
- 3.3-12mm AF lens
- Coaxial transmission for HD video and control signal
- Common 75-5 coaxial cables lossless transmission up to 300 meters
- High speed, long distance, real-time transmission
- ICR, dWDR, 3DNR, AGC, AWB, BLC, OSD
- TVI (default) / CVI / AHD/ CVBS output
- Cable OSD
- 5pcs IR Array, 50 meter
- IP66



SPECIFICATION	TWN-83MR
Pick Up Element	1/2" CMOS 8 Mega Pixels
Number of Pixels	3840(H)×2160(V)
Synchronisation	Internal
Resolution	8M
Video output	TVI:8M@15fps,1080P@25fps,4MP@25fps,5MP@20fps AHD:8M@15fps,1080P@25fps,4MP@25fps,5MP@20fp CVI:8M@15fps,1080P@25fps,4MP@25fps,5MP@20fps CVBS:PAL
Lens	3.3-12mm AF Lens
IR Series Distance	Max. 50 Meter with 5pcs IR Array
Minimum Illumination	0.01LUX(F1.2)
S/N Ratio	50dB(min)(AGC closed)
AE	GLOBE/BLC
WDR	dWDR
AWB	PRO/GRAY WORLD/ATW/MWB
3DNR	AUTO/MANUAL(0-10)
OSD	Yes
Language	English, Spanish, French, Polish, Italian, Portuguese
Day/Night	Auto,Color,MONO,Ext
Power	DC12V, 600mA
Transmission distance	75-5 300M
Operation Temperature	-20°C+55°C, Humidity less than 85%RH
Case Dimension	295(L)×91.7(W)×92.6(H)mm



DIMENSIONS

