

Item code: 70454-IWH-21LIX

Product description: IP BULLET Camera VALUE Series 2 MP

Main features: 2 MP IR Fixed Bullet Network Camera, 0.028 Lux/ (F2.0, AGC ON), 0 Lux with IR, 2 streams, 3D-DNR, ICR, EXIR 2.0, Built-in microphone, IP67.



SPECIFICATIONS

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Colour: 0.028 Lux@(F2.0, AGC ON), 0 Lux with IR
Shutter Speed	1/3 ÷ 1/100,000 s
Slow Shutter	Yes
Day & Night	IR Cut Filter
WDR	DWDR
Angle Adjustment	Pan: 0° ÷ 360°, tilt: 0° ÷ 180°, rotate: 0° ÷ 360°
Lens	
Lens Type	Fixed lens, 2.8/4 mm
Aperture	F2.0
Focal of View	Horizontal FOV: 114° Vertical FOV: 62° Diagonal FOV: 135°
Lens Mount	M12
IR	
IR Range	Up to 30m
Wavelength	850 nm
Video	
Max. Resolution	1920 × 1080
Main Stream	50 Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720) 60 Hz: 30 fps (1920 × 1080, 1280 × 960, 1280 × 720)
Sub Stream	50 Hz: 25 fps (640 × 480, 640 × 360, 320 × 240) 60 Hz: 30 fps (640 × 480, 640 × 360, 320 × 240)
Video Compression	Main stream: H.265+/H.265/H.264+/H.264 Sub-stream: H.265/H.264/MJPEG
H.264 Type	Baseline Profile/Main Profile/High Profile
H.265 Type	Main Profile
Video Bit Rate	32 Kbps ÷ 8 Mbps
Audio (-U)	
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM



BS OHSAS 18001:2007
Occupational Health and Safety Management System



ISO 9001:2015
Quality Management System



ISO 14001:2015
Environmental Management System



CI IPTI: 2015
100% Made in Italy Certificate



MAZi – Brand distributed by **LINCE ITALIA S.p.A.**
 Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
 Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 1 di 2

Audio Bit Rate	64 Kbps (G.711)/16 Kbps (G.722.1)/16 Kbps (G.726)/32-192 Kbps (MP2L2)
Smart Feature-Set	
Basic Event	Motion detection, video tampering alarm, exception (illegal login)
Linkage Method	Upload to FTP, notify surveillance center, send email, trigger capture
Region of Interest	1 fixed region for main stream and sub-stream
Image	
Image Enhancement	BLC, 3D-DNR
Image Settings	Rotate mode, saturation, brightness, contrast, sharpness, AGC and white balance adjustable by client software or web browser
Day/Night Switch	Day/Night/Auto/Schedule
Network	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, RTP, RTSP, RTCP, NTP, IGMP, QoS, UDP
API	ONVIF (PROFILE S, PROFILE G), ISAPI, SDK
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users 3 levels: Administrator, Operator and User
Client	CMS-MAZi
Web Browser	IE8+, Chrome 41.0-44, Firefox 30.0-51, Safari 8.0-11
Interface	
Communication Interface	1 RJ45 self-adaptive Ethernet port
Audio	1 audio input (built-in microphone), mono sound
Interface Style	Pigtail style interface
General	
Firmware Version	5.5.83
General Function	One-key reset, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter
Reset	Reset via web browser and client software
Startup and Operating Conditions	-30 °C ÷ 60 °C (-22 °F ÷ 140 °F), humidity 95% or less (non-condensing)
Storage Conditions	-30 °C ÷ 60 °C (-22 °F ÷ 140 °F), humidity: 95% or less (non-condensing)
Power Supply	12 Vdc ± 25%, Φ 5.5 mm coaxial power plug; PoE (802.3af, class 3)
Power Consumption and Current	12 Vdc, 0.4 A, max. 5 W PoE (802.3 af, 36 ÷ 57 V), 0.2 ÷ 0.1 A, max. 6.5 W
Material	Front cover: metal Back cover : plastic
Dimension	Camera: 67.8 × 66.2 × 177.6 mm (2.7" × 2.6" × 7") With package: 216 × 121 × 118 mm (8.5" × 4.8" × 4.6")
Weight	Camera: Approx. 270 g (0.6 lb.) With package: Approx. 470 g (1 lb.)