

Item code: 70403-IVH-22LIX

Product description: IP DOME Camera 2 MP

Main features: IP camera using 1/2.8" progressive scan CMOS image sensor, with 2.0 mega-pixel resolution. Support H.265+, H.265, H.264+, H.264, dual-stream. Max resolution: 1920x1080. Support Onvif. PoE, up to 30 m IR m, 2.8 mm lens. Metal and plastic DOME casing.



SPECIFICATIONS

Camera	
Model No.	IVH-22LIX
Image sensor	1/2.8" progressive scan CMOS
Minimum Illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON)
Shutter Speed	1/3 s to 1/100, 000 s
Slow Shutter	Yes
Auto-Iris	No
Day & Night	IR cut filter
Digital noise reduction	3D DNR
WDR	Digital WDR
Angle Adjustment	Pan: 0° to 360°, tilt: 0° to 75°, rotation: 0° to 360°
Lens	
Focal Length	2.8 mm
Aperture	F2.0
Focus	No
FOV	horizontal FOV 114.5° vertical FOV 62° diagonal FOV 135.5°
Lens Mount	M12
IR	
IR Range	Up to 30 m
Wavelength	850 nm
Compression Standard	
Video compression	Main stream: H.265/H.264 Sub stream: H.265/H.264/MJPEG
H.264 Type	Baseline Profile/Main Profile/High Profile
H.264+	Main stream supports
H.265 Type	Main Profile
H.265+	Main stream supports
Video Bit Rate	32 Kbps to 8 Mbps
Smart Features	
Region of Interest	1 fixed region for main stream and sub-stream
Image	
Max. Resolution	1920 x 1080



BS OHSAS 18001:2007
Occupational Health and Safety Management System



ISO 9001:2015
Quality Management System



ISO 14001:2015
Environmental Management System



CI ITPI: 2015
100% Made in Italy Certificate



MAZi – Brand distributed by **LINCE ITALIA S.p.A.**
 Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
 Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net - info@lince.net
MD-03.11 Rev. 6 - Pag.: 1 di 2

Main Stream Max. Frame Rate	25fps (1920 × 1080, 1280 × 960, 1280 × 720)
Sub-stream Max. Frame Rate	25fps (640 × 480, 640 × 360, 320 × 240)
Image Enhancement	BLC, 3D DNR
Image Setting	Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser
Day/Night Switch	Auto, scheduled
Network	
Alarm Trigger	Motion detection, video tampering alarm, illegal login
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
General Function	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark
API	ONVIF (PROFILE S, PROFILE G), ISAPI
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users, 3 levels: Administrator, Operator and User
Client	CMS-MAZi, Guarding Vision
Web Browser	IIE7+, Chrome18-42, Firefox5.0+, Safari5.02+
Interface	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
General	
Operating Conditions	-30 °C ÷ 50 °C , Humidity 95% or less (non-condensing)
Power Supply	12 Vdc ± 25%, 5.5 mm coaxial power plug PoE (802.3af, class 3)
Power Consumption and current	12 Vdc, 0.4 A, max: 5 W PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.1 A, Max: 6.5 W
Ingress Protection	IP67
Material Dimensions	Metal & Plastic Camera: Ø 110 mm × 93.2 mm With package: 150 × 150 × 141 mm
Dimensions	Camera: Ø 110 mm × 93.2 mm With package: 150 × 150 × 141 mm
Weight	Camera: ~ 360 g With package: ~ 610 g