

TWN-43VR

4 in 1 HD TVI BULLET



KEY FEATURES

- High performance CMOS, 4 Mega Pixel
- Support coaxial transmission for HD video and control signal
- Support common 75-3 similar coaxial cables lossless transmission up to 300 meters
- High speed, long distance, real-time transmission
- ICR, 2D-DNR, dWDR, BLC, Mirror
- 5pcs IR Array, 50 meter
- IP66
- 2.8-12mm lens
- TVI (default) / CVI / AHD/ CVBS output



SPECIFICATION	TWN-43MR
Pick Up Element	1/3"CMOS 4 Mega Pixels
Number of Pixels	2560(H)×1440(V)
SYNC.	Internal
Resolution	4MP(25fps) 1080P
Video Output	TVI (Standard)/AHD/CVI/CVBS
Lens	2.8-12mm
IR Series Distance	Max.50 Meter with 5pcs array IR Array
Power supply	DC12V,450mA
Minimum Illumination	0.01Lux(F1.2)
Electric Shutter	1/25s-1/10000s
S/N Ratio	48dB(min)(AGC closed)
MIRROR	DEFAULT/H/V/HV
DNR	2D-DNR 1-10
WHITE Balance	ATW/MWB
AE MODE	GLOBE/BLC
WDR	dWDR
Coaxial	Yes
Language	English, Italian, Spanish
Day/Night	Ext Color, B/W
Transmission distance	75-5 300M
Water Resistance	IP66
Dimension (mm)	295(L)×91.7(W)×92.6(H)mm
Storage Temperature	-30~ +60°C RH95% Max
Operating Temperature	-20~ +50°C RH95% Max



DIMENSIONS

