

IWE-42IR

NETWORK OUTDOOR BULLET IR



KEY FEATURES

- 1/3" 4M CMOS
- H.264/H.265 Encoding, 2D/3D DNR, Motion Detection
- 3.6mm lens
- 3pcs IR Array up to 40 meter
- DC 12V/PoE, ICR, IP66



SPECIFICATION	IWE-42IR
Camera	
Sensor	1/3" 4M CMOS
Min Illumination	0.01Lux@F1.2 (0Lux,IR on)
S/N	≥50dB(AGC OFF)
IR LEDs	3 pcs IR Array
IR Range	40m
Lens	3.6mm
Current	480mA
Power Consumption	<5W
Weight	480g
IP Rating	IP66
Interface	
Ethernet	RJ45 10M/100M
Audio Input	1CH Audio Input
Video Encoding	
Encoding	H.264, H.265, MJPEG
Main Stream resolution	15fps@2592*1520, 25(30)fps@2048*1520, 25(30)fps@1920*1080
Sub Stream resolution	25(30)fps@704*576, 25(30)fps@640*480 25(30)fps@640*352, 25(30)fps@320*240
Video Compression	32Kbps-16Mbps Continuously adjustable, CBR/VBR supported
Subtitle Overlay	Channel Name, Date&Time,Stream Information Overlay, Overlay Position adjustable
Data Transfer and Storage	
Data Storage	Video, Image
Storage Mechanism	Manual, Auto (Loop, Timing, Motion detection)
Alarm message	FTP, E-mail, Browser, Management Software
Network Protocol	TCP/IP,UDP,RTSP,RTCP,HTTP,DNS,DDNS,DHCP FTP,NTP,PPPOE,SMTP,UPNP
Client-side Browse	Support Windows Mobile,iPhone,iPad,Android platforms
ONVIF Protocol	ONVIF 2.2
General Parameters	
Input Voltage	DC12V±10%/PoE
Working Temperature	-20°C +50°C
Working Humidity	<90%RH(No Condensation)



Optional Accessory



IJ-W100E

DIMENSIONS (mm)

