

TWC-22VRLP

HD TVI POC IR BULLET



KEY FEATURES

- 2.0 megapixel high-performance CMOS
- HD analog output, up to 1080p resolution
- 2.8 mm to 12 mm vari-focal lens
- True Day/Night
- Up to 40 m IR distance
- IP66
- PoC.at
- Up the Coax
- No OSD



SPECIFICATION	TWC-22VRLP
Camera	
Image Sensor	2.0 megapixel progressive scan CMOS
Signal System	PAL/NTSC
Frame Rate	1080p@25fpS
Effective Pixels	1920 (H) × 1080 (V)
Min. illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/25 s to 1/50,000 s
Lens	2.8 mm to 12mm vari-focal lens
Horizontal Field of View	105.2° to 32.8 °
Lens Mount	M14
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, Tilt:0° to 90°, Rotate: 0° to 360°
Synchronization	Internal synchronization
S/N Ratio	> 62 dB
Interface	
Video Output	1 HD analog output
General	
Operating Conditions	-40 °C to 60 °C, humidity: 90% or less (non-condens.)
Power Supply	12V DC±30%/PoC.at
Power Consumption	Max. 6.5 W
Ingress Protection	IP66
Material	Metal
IR Range	Up to 40 m
Dimensions	92 mm × 89 mm × 269.6 mm
Weight	Approx. 900 g



DIMENSIONS:

