

IWN-22VRL

IP BULLET



KEY FEATURES

- High performance OV CMOS, 2M resolution
- **Waterproof RJ45**
- H.264, dual-stream
- **Max resolution:1920*1080**
- Onvif and P2P supported
- dWDR, IR Cut Filter, IP66
- 3pcs IR Array, up to 40 meter
- 2.8-12mm lens



SPECIFICATION	IWN-22VRL
Sensor	1/2.9" SONY CMOS
Min Illumination	Color 0.1Lux@F1.2,white/black 0.01 Lux@F1.2
WDR Range	dWDR Range >80db
Video processing	H.264,dual-stream,CBR/VBR,32K~16M bit/S adjustable; 1-30fps adjustable
Main stream	1920*1080, 1-25fps 1280*720, 1-25fps
Sub stream	720*576, 1-25fps ; 640*480, 1-25fps 640*352, 1-25fps; 320*240, 1-25fps
Audio interface	Support 1 channel linear audio input; 1channel audio output
Audio processing	G.711 coding Standard,Support bothway Voice intercom function,support the synchronization of audio and video
Network Port	1 RJ45 ethernet network port, 10M/100M self-adaption
Network protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP
IR linkage	support
Operation function	Support Web setting, OSD, real-time video transmission, support motive detection and IO alarm linkage for front end shortage/Capture, Support Central remind and image linkage after motion detection and IO alarm linkage, support MJPEG capture, Support unit clint-side remote management software, provide complete SDK
Standard protocol	Onvif 2.4
Mobile monitor	Support P2P, (IOS, Android)
Power supply	DC10.8V~13.2V, 650mA
Working temperature	-20C~55C
Protection rate	ESD 1kv
IR Series Distance	Max. 40 Meter with 3pcs IR Array
Lens	2.8-12mm varifocal lens
Camera size	277.5mm(L)*79MM(H)



DIMENSIONS

