

**Item code:** 70393-IWN-23IR5

**Product description:** IP Bullet Camera 2 MP

**Main features:** IP camera using high performance CMOS image sensor, with 2.0 mega-pixel resolution. Support H.264, dual-stream. Max resolution: 2592x1520. Support Onvif, P2P, support ICR switching. PoE, 2 pcs array IR, IR range 20 m, 2.8 mm lens. Metal Bullet casing.



### SPECIFICATIONS

Model No.	IWN-23IR5	
Sensor	HI3516C V200 1/2.9" SONY IMX323	
Minimum Illumination	Color 0.1 Lux@F1.2, black and white 0.01 Lux@F1.2	
Signal to noise ratio	≥50 db (AGC OFF)	
WDR	DWDR <input type="checkbox"/> range <input type="checkbox"/> 80 db	
Code form	H.264 Baseline, Main Profile, High Profile code, MJPEG code	
Image output	<i>Main stream</i>	1920x1080, 1-25(30)fps/s, 1280x720, 1-25(30)fps/s 720x576, 1-25(30)fps/s, 640x480, 1-25(30)fps/s
	<i>Second stream</i>	640x352, 1-25(30)fps/s, 320x240, 1-25(30)fps/s
Video compression rate	Support dual stream; support CBR/VBR bit rate, 32 K~16 M bit/S adjustable; frame rate 1-30fps/s adjustable	
Network Interface	1 RJ45 Ethernet interface, 10/100 M adaptive;	
Network protocol	Supports network protocols such as RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP;	
USB interface	A USB interface that can be used for U disk storage or TF storage by adding SD card expansion board. Supports up to 128 G.	
TF card storage	Add SD card expansion board to achieve TF storage. Support 128 G maximum.	
Automatic aperture	No	
Infrared light linkage	Yes	
PTZ interface	No	
CVBS output	No	
3G transmission	No	
WiFi transmission	No	
PoE power supply	support	
Standard agreement	ONVIF	
Phone monitoring	Support P2P <input type="checkbox"/> Support mobile device monitoring <input type="checkbox"/> iOS <input type="checkbox"/> Android <input type="checkbox"/>	
Operation Temperature	-10 <input type="checkbox"/> ÷ 55 <input type="checkbox"/>	
Camera size (LxWxH)	188×63.5×63.5 mm	
Camera weight	320 g	