

IVH-42LI-UH

4 MP Fixed Turret Network Camera.

High quality imaging with 4 MP resolution
Support Human and Vehicle Detection
Smart Hybrid Light: advanced technology with long range
Built-in microphone for real-time audio security
Efficient H.265+ compression technology
Support on-board storage up to 512 GB (SD card slot) (Optional)
Water and dust resistant (IP67)

Camera	
Image Sensor	1/3" Progressive Scan CMOS
Max Resolution	2560 x 1440
Min. Illumination	Colour: 0.005 Lux @(F1.6; AGC ON), B/W: 0 Lux with IR
Shutter Time	1/3 ÷ 1/100,000 s
Day &Night	IR Cut Filter
Angle Adjustment	Pan: 0° ÷ 360°, Tilt: 0° ÷ 75°, Rotate: 0° ÷ 360°
Lens	
Lens Type	Fixed focal lens, 2.8 mm
Focal Length & FOV	2.8 mm, horizontal FOV 98°, vertical FOV 54°, diagonal FOV 114°
Lens Mount	M12
Iris Type	Fixed
Aperture	F1.6
DORI	
DORI	2.8 mm, D: 63 m, O: 25 m, R: 12 m, I: 6 m
Illuminator	
Supplement Light Type	IR, White Light
Supplement Light Range	Up to 30 m
Smart Supplement Light	Yes
IR Wavelength	850 nm
Video	
Main Stream	50 Hz: 20 fps (2560 × 1440); 25 fps (1920 × 1080, 1280 × 720) 60 Hz: 20 fps (2560 × 1440); 24 fps (1920 × 1080, 1280 × 720)
Sub-Stream	50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360) 60 Hz: 24 fps (1280 × 720, 640 × 480, 640 × 360)
Video Compression	Main stream: H.265+/H.265/H.264+/H.264 Sub-stream: H.265/H.264/MJPEG
Video Bit Rate	32 ÷ 8 Mbps
H.264 Type	Baseline Profile, Main Profile, High Profile
H.265 Type	Main Profile
Bit Rate Control	CBR, VBR
Region of Interest (ROI)	1 fixed region for main stream
Audio	

Audio Type	Mono sound
Environment Noise Filtering	Yes
Audio Sampling Rate	8 kHz/16 kHz
Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC-LC
Audio Bit Rate	64 Kbps (G.711 ulaw)/64 Kbps (G.711 alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 ÷ 160 kbps (MP2L2)/16 ÷ 64 kbps (AAC-LC)
Network	
Security	Password protection, complicated password, watermark, basic and digest authentication for HTTP, WSSE and digest authentication for Open Network Video Interface, security audit log, host authentication (MAC address)
Simultaneous Live View	Up to 6 channels
API	Open Network Video Interface (Profile S, Profile T, Profile G (only -F model supports)), ISAPI, SDK
Protocols	TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP
User/Host	Up to 32 users; 3 user levels: *administrator, operator, and user*
Client	CMS-MAZi; CTR-MAZi
Web Browser	Plug-in required live view: IE 10, IE 11, Local service: Chrome 57.0+, Firefox 52.0+
Image	
Wide Dynamic Range (WDR)	120 db
SNR	≥ 52 dB
Day/Night Switch	Day, Night, Auto, Schedule
Image Enhancement	BLC, HLC, 3D-DNR
Image Settings	Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance, adjustable by client software or web browser
Privacy Mask	4 programmable polygon privacy masks
Interface	
Ethernet Interface	1/3" Progressive Scan CMOS
On-Board Storage	-F: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Built-in Microphone	Yes
Reset Key	-F: Yes
Event	
Basic Event	Motion detection (support alarm triggering by specified target types (human and vehicle), video tampering alarm, exception
Linkage	Upload to FTP/memory card (-F), send email, notify surveillance center, trigger recording (-F), trigger capture
General	
Power	12 Vdc ± 25%; 0.4 A, max. 5 W; Ø 5.5 mm coaxial power plug, reverse polarity protection, PoE: IEEE 802.3af, class 3; max. 6.5 W
Material	Metal & Plastic
Dimension	*Camera*: Ø110 × 89.2 mm (Ø 4.3" × 3.5") *Package*: 150 × 150 × 141 mm (5.9" × 5.9" × 5.6")
Weight	*without package:* ~ 340 g (0.7 lb.); *with package* ~ 560 g (1.2 lb.)
Storage Conditions	-30 °C ÷ +60 °C (-22 °F ÷ +140 °F), Humidity 95% or less (non-condensing)
Operating Conditions	-30 °C ÷ +60 °C (-22 °F ÷ +140 °F), Humidity 95% or less (non-condensing)
Language	English, Ukrainian
General Function	Heartbeat, anti-banding, mirror, password protection, password reset via email

Approval	
EMC	FCC: 47 CFR Part 15, Subpart B, CE-EMC: EN 55032: 2015, EN 61000-3-2:2019, EN 61000-3-3: 2013+A1:2019, EN 50130-4: 2011 +A1: 2014, RCM: AS/NZS CISPR 32: 2015, IC: ICES-003: Issue 7
Safety	UL: UL 62368-1, CB: IEC 62368-1: 2014+A11, CE-LVD: EN 62368-1: 2014/A11: 2017, BIS: IS 13252 (Part 1): 2010/IEC 60950-1: 2005
Environment	CE-RoHS: 2011/65/EU, WEEE: 2012/19/EU, Reach: Regulation (EC) No 1907/2006
Protection	IP67: IEC 60529-2013

